

Randall

[45] **Date of Patent:** Aug. 17, 1999

- | | | | |
|-----------|---------|-------------------|---------|
| 4,583,668 | 4/1986 | Maynard, Jr. | 222/568 |
| 4,811,871 | 3/1989 | Wass et al. | 222/477 |
| 5,139,182 | 8/1992 | Appla | 222/547 |
| 5,141,138 | 8/1992 | Odet et al. | 222/547 |
| 5,219,100 | 6/1993 | Beck et al. | 222/556 |
| 5,320,260 | 6/1994 | Song et al. | 222/547 |
| 5,392,938 | 2/1995 | Dubach | 215/254 |
| 5,454,489 | 10/1995 | Vesborg | 222/547 |
| 5,497,906 | 3/1996 | Dubach | 222/23 |
| 5,531,363 | 7/1996 | Gross et al. | 222/547 |
| 5,782,388 | 7/1998 | De Nervo | 222/556 |

Attorney, Agent, or Firm—Rockey, Milnamow & Katz, Ltd.

Aspur-resistant spout for a dispensing structure includes (1) an internal tubular portion having a through bore connecting a dispensing orifice of the spout with the interior of the container, and (2) a surrounding wall portion surrounding the tubular portion. The tubular portion and the surrounding wall portion are sized and located so that little or no fluid is retained in and across the spout bore so as to prevent, or minimize, obstruction of the bore.

[56] **References Cited**

3,091,373	5/1963	Kirschenbaum	222/547
3,117,701	1/1964	Stull	222/571
3,563,422	2/1971	Cruikshank	222/547
3,833,150	9/1974	Visser-Patings	222/571
3,980,211	9/1976	Owens	222/547
4,427,138	1/1984	Heinlein	222/546

